Skgnall



www.DX-marine.com DESIGN BY DX-MARINE

Hand Flare



Standard: SOLAS 1974 as amended

Luminous intensity: 15000cd

Flame colour: red

Burning time: ≥60s

Validity: 3 years

Other signals: white, green, blue

Approve: CCS MED EC SOLAS

Lifebuoy Self-igniting Light and Self-activating Smoke Signals



Standard: SOLAS 1974 as amended

Light Output: ≥2cd

Light duration: ≥2h

Smoke colour: orange

Emitting duration: ≥15min

Approve: CCS MED EC SOLAS



Rocket Parachute Flares

Standard: SOLAS 1974 as amended

Luminous intensity: 30000cd

Flame colour: red

Launching heght: 300m

Burning time: ≥40s

Validity: 3 years

Approve: CCS MED EC SOLAS

DX-marine

Line Throwing Unit



Standard: SOLAS 1974 as amended

The assembly of an integral

pistol-fired rocket and line is

contained in water-resistance case

Throwing length: 270m

Throwing distance (in calm weather):

≥230m

Breaking strength: ≥2.0KN

Deflection: 10 degrees from center

line

Approve: CCS MED EC SOLAS

Buoyant Smoke Signals



Standard: SOLAS 1974 as amended

Smoke colour: orange

Emitting duration: 3mins

Other signals: white, red, yellow,

blue, black

Validity: 3 years

Approve: CCS MED EC SOLAS



Line Throwing Appliance

Standard: SOLAS 1974 as amended

Comprised of 1 line throwing gun, 4 projectiles and 4 lines

Length of throwing lines: 270m

Throwing distance (in calm weather): ≥230m

Breaking strength: ≥2.0KN

Deflection: 10 degrees from center line

Projectile: 3 years

Throwing pistol: 9 years

Approve: CCS MED EC SOLAS



Warning

Use for distress signal only.

Don't direct outlet to person.

Use before the expiry date.









Jiangsu Dingxiang Marine Equipment Co.,LTD.

Professional fire fighting & life saving equipment manufacturer