

Fireproof lifeline



www.DX-marine.com

DESIGN BY DX-MARINE

A、 *Standard*

SOLAS 1974, as amended

B、 *Technical parameter*

- Length : 40m
- Diameter : 12mm
- Weight: 3.3kg
- Breaking load : 5 kN
- Material : The inner core of $\Phi 4.2$ mm aviation steel wire rope, outsourcing double braided twine, elastic hook is made of stainless steel.



C、 *Application*

This product is widely used in fire fighting equipment, military exercises, high-rise residential, outdoor climbing rock climbing downhill Hotel , hotels, shopping malls, office buildings, public entertainment and other emergency fire rescue, escape rescue products necessary.

D、 *Instructions*

- Take out the fireproof lifeline and hang the safety hooks on the fixed frame or any stable support.
- Cast the fireproof lifeline to the floor outside the building to relieve the ropes.
- Put the fireproof lifeline safety harness under the arm and tighten the slide fastener to a suitable position.
- From the window or platform, facing the wall with a fireproof lifeline to fall.
- After landing, quickly loosen the slide of the fireproof lifeline, take off the seat belt and leave the site.
- In special circumstances, the fireproof lifeline can support and hold a child facing the wall.
- Attention: Only scratch down the fireproof lifeline itself, do not catch another rope.

E、 *Approved: CCS*

Jiangsu Dingxiang Marine Equipment Co.,LTD.

Professional fire fighting & life saving equipment manufacturer