

# 9L AFFF Foam Fire Extinguisher (stored pressure)



[www.DX-marine.com](http://www.DX-marine.com)

DESIGN BY DX-MARINE



Type : PSMFZ9F

Extinguishant: 3% AFFF Foam

Capacity (L): 9

Propellant: Dry Nitrogen(N2)

Cylinder Diameter (mm): 180

Overall Height (mm) : 610

Approx Full Weight (kg): 14.1

Working Temp. Range: 0°C to + 60°C

Working Pressure (20°C): 10 Bar

Test Pressure: 27 Bar

Burst Pressure: Exceeds 55 Bar

Approx Discharge Range (m): >4

Approx Discharge Time (sec): ≥15

Fire Rating: 21A 183B C

Fire Class: A B C

Cylinder Specification: CE EN3-8

Discharge Assembly: PVC Nozzle

Mounting: Wall hanger

Operating Head / Valve: Brass nickel plating

Paint Finishing: RAL 3000 Flame Red

Thermoset polyester

Manufactured & Certified to: CE EN 3-7 + EN 3-8

Approved: MED CE EN3



Bottle holder



Service record

**Jiangsu Dingxiang Marine Equipment Co.,LTD.**

**Professional fire fighting & life saving equipment manufacturer**